

LINE 50 3-PHASE TRACK SYSTEM

LI50T-129401-HOWHM

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Housing Color: white
 RAL: similar to RAL 9016
 Protection rating: IP20
 Protection Class: Class I

LED

Luminous Flux: 2767 lumen
 Output: LED high Output
 Colour temperature: 4000K
 CRI: > 90
 Lifetime: L80 B10 75.000h
 Energy efficiency class: D

OPTICS

Light Emission: direct
 Optics: Cover PMMA microprism

ELECTRICS

Power: 30 watt
 Dimmability: on/off
 Circuit breaker type C13: 28pcs.
 Voltage: 220-240V 50/60Hz


DIMENSIONS

Length: 1214 mm
 Width: 50 mm
 Height: 80.5 mm
 Weight: 2.9 kg



LINE 50 3-Phase Track System luminaire made of extruded aluminium profile; luminaire with fine-textured matt white powder-coated finish - similar to RAL 9016; direct light emission; incl. LED driver on/off; light control directly through Cover PMMA microprism; LED high Output option with a System luminous flux of 2767lm at 30W; colour temperature 4000K; CRI > 90; Binning initial MacAdam ≤ 3 SDCM; retinal blue light hazard according to IEC TR 62778 risk group RG 1 (unlimited) - no risk; Lifetime: L80 B10 75.000h; protection type IP20; protection class I; dimensions: LxWxH: 1214 mm x 50 mm x 80.5 mm; Weight: 2.9 kg; light source and driver replaceable by a qualified electrician

LIGHT DISTRIBUTION



DRAWING

