

LINE 50 SUSPENDED

LI50H-199401-HOBLM

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Housing Color: black
 RAL: similar to RAL 9005
 Protection rating: IP20
 Protection Class: Class I

LED

Luminous Flux: 4427 lumen
 Output: LED high Output
 Colour temperature: 4000K
 CRI: > 90
 Lifetime: L80 B10 75.000h
 Energy efficiency class: D

OPTICS

Light Emission: direct
 Optics: Cover PMMA microprism

ELECTRICS

Power: 46.3 watt
 Dimmability: on/off
 Circuit breaker type C13: 28pcs.
 Voltage: 220-240V 50/60Hz


DIMENSIONS

Length: 1934 mm
 Width: 50 mm
 Height: 80.5 mm
 Weight: 4.6 kg
 Pendulum length: 2000 mm



LINE 50 Suspended made of extruded aluminium profile; luminaire with fine-textured matt black powder-coated finish - similar to RAL 9005; direct light emission; through-wiring 5-pole; incl. LED driver on/off; light control directly through Cover PMMA microprism; incl. white canopy with transparent power feed cable as well as flexibly positionable suspension cable hangers (2000mm) and quick-release clamps for infinitely variable adjustment of the mounting height; LED high Output option with a System luminous flux of 4427lm at 46.3W; colour temperature 4000K; CRI > 90; Binning initial MacAdam ≤ 3 SDCM; retinal blue light hazard according to IEC TR 62778 risk group RG 1 (unlimited) - no risk; Lifetime: L80 B10 75.000h; protection type IP20; protection class I; dimensions: LxWxH: 1934x50x80.5mm; Weight: 4.6kg; light source and driver replaceable by a qualified electrician

LIGHT DISTRIBUTION



DRAWING

